



less'n'more

Athene Wall Light A-MWL2 alu touchdimmer arm white

Technical details

Country of Manufacture	 Germany
Manufacturer	less'n'more
Designer	less'n'more
Year of design	2021
Protection class / IP rating	IP43
Contents of the package	LED
voltage suitability	230 - 240 Volt
material	aluminum, glass
surface	aluminum
beam angle	25 - 100 degrees
dimming	Push button dimmer on the wall bracket
Wattage	4.8 W
LED	inclusive
Colour Rendering Index	90
Luminous flux in lm	600
Color temperature in Kelvin	2,700 extra warm white
flexible_arm	textile white
light head dimensions	7 cm
bulb exchange	on site itself
Wall mount dimensions	7 cm
Dimensions	H max. 59 cm

Description

The Less'n'more Athene Wall Light A-MWL2 is installed into the wall and has an aluminum mounting plate as wall bracket. The mounting plate has a diameter of 6.5 cm and can be installed freely by 360 degrees when mounted. This is a lamp for mounting on cavity wall box, its external transformer is built into the wall. A mounting plate is available as an accessory, with which the lamp can also be mounted on a flush-mounted box.

The flexible lamp arm of the Athene Wall Light A-MWL2 can be stretched and bent as desired. With a maximum alignment of the lamp arm, the lamp is 59 cm high. The flexible lamp arm is offered in these colours: aluminum, textile black, white, anthracite, blue, green, red and brown. The integrated LED has an output of 6 watts and a colour temperature of 2,700 Kelvin extra warm white.

Lamp head and wall bracket are available in the surfaces aluminum, black and white. The beam angle of the light can be adjusted in steps between 25 and 100 degrees. All you have to do is turn the glass lens out of or into the lamp head. The beam angle determines the angle at which the light emerges from an LED spotlight. The larger the beam angle, the larger the illuminated area, but it is also less bright because more area is illuminated.

This Athene recessed lamp is offered dimmable on site with a trailing edge phase dimmer or with a built-in push button dimmer on the wall bracket. The flexible lamp arm is available in other colours on request. The lamp is also offered on request with a supply cable and safety plug to be connected directly to a power supply.