



Lichtlauf

UpLight Down

Durchmesser in cm

- 40
- 50
- 30

Kabelfarbe

- red
- white
- grey

Technical details

Country of Manufacture	 Germany
Manufacturer	Lichtlauf
Designer	Christoph Matthias
Year of design	2012
Protection class / IP rating	IP20
Contents of the package	Leuchtmittel/ Bulb
voltage suitability	110 - 240 Volt
material	polyethylene, Textile
surface	white
Cable length	250 cm
dimming	dimmable on site
Base / Socket	E27
Switchability	on the lead
Power (max. Watt)	70 Watt
bulb exchange	on site itself

Description

The UpLight Down light run is the floor version of the UpLight lamp. Supplemented with a stand ring and foot switch, this lamp illuminates low room zones with its mild light, creating a special and variable lighting mood. The white hollow sphere made of resistant and high-quality polyethylene is available in three different diameters, the textile cable in three different colours. The UpLight Down by Lichtlauf has an E27 ceramic socket and can be operated with conventional halogen bulbs as well as with LED retrofit bulbs. This portable lamp is available with a diameter of 30 cm, 40 cm or 50 cm. The textile 2.5 m cable is optionally available in white, red or grey. On request, the textile cable is also available in other colours and lengths.