



Lichtlauf

Lichtenfest 100

Oberfläche

- copper
- Silver
- gold
- white

Dimmbarkeit

- DALI dimmable
- on site dimmable with a trailing edge dimmer

Description

The Lichtlauf Lichtenfest 100 consists of three layers of leaf-metallised metal formed into a volume. The Lichtenfest by the German manufacturer Lichtlauf emits light downwards and between the three layers of the lampshade, which is formed into a volume, also reflected into the room. Between the three layers of the lampshade, an intensive glow is created by multiple reflection. Each Lichtlauf Lichtenfest lamp is individually handmade and unique. Due to the handcrafted manufacturing process, there may be irregularities in the leaf-finished surface. The two integrated LEDs, each with an output of 12 watts, have a colour temperature of 3,000 Kelvin warm white. The light of the LEDs of this dimmable lamp is characterised by a very good colour rendering with a high colour rendering index of Ra 90. The Lichtlauf Lichtenfest is available in the surfaces copper and white matt. This pendant lamp is suspended from the ceiling canopy by a thin wire cable. The height is adjusted directly on the ceiling canopy. The transparent 250 cm long cable, which serves as a supply line, can be shortened if necessary. This LED pendant lamp is available as an on-site dimmable version with a phase cut-off dimmer or DALI dimmable version. The lampshade of the Lichtenfest 100 has a diameter of approx. 100 cm. The Lichtenfest is also available in other sizes. Special sizes are possible for all Lichtenfest lamps, also special colours and other cable lengths are available on request. On request, the surface can also be covered with real gold, platinum or moon gold. Prices on request.

Technical details

Country of Manufacture	 Germany
Manufacturer	Lichtlauf
Designer	Christoph Matthias
Year of design	2005
Protection class / IP rating	IP20
Contents of the package	LED
voltage suitability	230 - 240 Volt
Diameter in cm	100
material	aluminum
cable color	transparent
Cable length	250 cm
Height adjustment	height determinable
LED	inclusive
Colour Rendering Index	90
Color temperature in Kelvin	3,000 warm white
bulb exchange	at the manufacturer / at the factory
system performance	2 x 12 Watt
Dimensions	Ø 100 cm